SG5.0-20RT

COMPATIBILITY OVERVIEW






Communication

	Part of delivery	Max. Support	Features / Comment
WiNet-S	yes	max. 1 device	10 sec. refresh, WiFi or Ethernet
COM100E	no	max. 5 devices**	FTP push, connecting environm. sensors, daisy chain mode, WiFi or Ethernet

Energy Meters

* only with meter version bought from Sungrow




** devices: inverters, energy meters, and irradiation sensors



SH6.0-10RT

COMPATIBILITY OVERVIEW







SH15-25T

COMPATIBILITY OVERVIEW



	Communication			
PETER		Part of delivery	Max. Support	Features / Comment
	WiNet-S2	yes	max. 1 device	10 sec. refresh, WiFi or Ethernet
	Energy Meters	Part of delivery	Feed-in limitation	Features / Comment
(4 : 0 to 0	DTSU666 5(80)A*	no	yes, 1 per host inverter	
	DTSU666-20* * only with meter version bought from Sur	yes	yes, 1 per host inverter	3x 100 A / 330 mV CT included, 3x 250 A / 330 mV CT to be purchased separately
	Battery			
	SBR096-256	no	max.1 stack	The modular design allows to stack from 3 to 8 modules
	SBH100-400	no	max.1 stack	The modular design allows to stack from 2 to 8 modules



SG33-125CX-P2

COMPATIBILITY OVERVIEW



Communication





	Part of delivery	Max. Support	Features / Comment
WiNet-S	no	max. 1 device	10 sec. refresh, WiFi or Ethernet
COM100E	no	max. 30 devices**	FTP push, connecting environm. sensors, daisy chain mode, WiFi or Ethernet

Energy Meters

Janitza



	Part of	Feed-in limitation	Features / Comment
	delivery		
DTSD1352 6A*	no	WiNet-S : max. 1 device COM100E: max. 30 devices** (SG33-50CX-P2)	CT from 3rd party manufacturer

WiNet-S (only UMG604): max. 1 device





(UMG)	110	COM100E (UMGxx): max. 30 devices**
Weidmüller (EM610)	no	WiNet-S : max. 1 device COM100E: max. 30 devices**
DTSU666*	no	WiNet-S : max. 1 device (only SG25-SOCX-P2) COM100E: max. 30 devices**
DTSU666-20*	no	WiNet-S: max. 1 device (only SG25-SOCX-P2) COM100E: max. 30 devices**
		•

^{*} only with meter version bought from Sungrow ** devices: inverters, energy meters, and irradiation sensors

3rd party manufacturer

3rd party manufacturer

Currently, direct connection of DTSU666(-20) in single inverter scenarios only available for SG25-50CX-P2

SG33-110CX

COMPATIBILITY OVERVIEW



Communication



	Part of	Max. Support	Features / Comment
	delivery		
WiNet-S	no	max. 1 device	10 sec. refresh, WiFi or Ethernet
COM100E	no	max. 30 devices**	FTP push, connecting environm. sensors, daisy chain mode, WiFi or Ethernet
EyeM4	no	max. 10 devices**	Daisy chain mode, WiFi

Energy Meters

Part of



	delivery		
DTSD1352 6A*	no	COM100E: max. 30 devices** (sc33-50cx) COM100E: max. 25 devices** (sc110cx) EyeM4: max. 10 devices**	CT from 3rd party manufacturer
Janitza (UMG)	no	COM100E (<i>UMGxx</i>): max. 30 devices** EyeM4 (<i>only UMG604</i>): max. 10 devices**	3rd party manufacturer
Weidmüller (EM610)	no	COM100E: max. 30 devices** EyeM4: max. 10 devices**	3rd party manufacturer

Feed-in limitation



Features / Comment

^{*} only with meter version bought from Sungrow

^{**} devices: inverters, energy meters, and irradiation sensors