

Three phase hybrid inverters 15 to 30 kW

ASW TH Series



Models:
ASW015K-TH
ASW020K-TH
ASW025K-TH
ASW29.9K-TH
ASW030K-TH



Optimal performance

- 4 MPPTs, up to 40 A input per MPPT
- Up to 200 % PV array oversizing
- Up to 100 A charge / discharge current
- ShadeSol shadow management
- Dynamic export power control



Safe and reliable

- String-level current monitoring
- DC SPD Type II surge protection
- IP66 rated design for indoor and outdoor use
- Optimal battery voltage range, 120-800 V
- Intelligent operation modes and smart battery management
- UPS-level switching time < 10 ms



User-friendly

- Quick and easy-to-install with standard tools
- Cover design, choice from a delightful range of colours
- Smart setup, commissioning and monitoring via Solplanet App
- Anti-theft design

Technical Datasheet

ASW015K-TH

ASW020K-TH

ASW025K-TH

ASW29.9K-TH

ASW030K-TH

PV input	Max. PV array power	30000 Wp	40000 Wp	50000 Wp	59800 Wp	60000 Wp
	Max. input voltage	1000 V				
	MPP voltage range / rated input voltage	150 V to 950 V / 630 V				
	Min. input voltage / start voltage	95 V / 180 V				
	No. of independent MPPT trackers / strings per MPPT input	4 / 1		4 / 2		
	Max. input current / Max. power per MPP tracker	20 A / 15000 W	20 A / 15000 W	40 A / 25000 W	40 A / 25000 W	40 A / 25000 W
	Max. short-circuit current per MPP tracker	25 A		50 A		
Battery input	Battery voltage range	120 V to 800 V				
	Max. charge power from PV and AC side	30000 W	40000 W	50000 W	59800 W	60000 W
	Max. charge power from AC side	15000 W	20000 W	25000 W	29900 W	30000 W
	Max. discharge power	15000 W	20000 W	25000 W	29900 W	30000 W
	Max. charge current / Max. discharge current	50 A		100 A		
	No. of independent battery inputs	1		2		
AC input	Battery type	LiFePO4				
	Nominal AC voltage	3/N/PE, 220 V / 380 V 3/N/PE, 230 V / 400 V 3/N/PE, 240 V / 415 V				
	Rated grid frequency	50 Hz / 60 Hz				
	Max. input power from grid	30000 W	40000 W	50000 W	50000 W	50000 W
	Max. input current from grid	43.5 A	58.0 A	72.5 A	72.5 A	72.5 A
AC output	Nominal AC voltage	3/N/PE, 220 V / 380 V 3/N/PE, 230 V / 400 V 3/N/PE, 240 V / 415 V				
	AC voltage range	270 V to 480 V				
	Rated AC grid frequency	50 Hz / 60 Hz				
	AC grid frequency range	45-55 Hz / 55-65 Hz				
	Rated apparent power	15000 VA	20000 VA	25000 VA	29900 VA	30000 VA
	Max. apparent power	16500 VA	22000 VA	27500 VA	32890 VA	33000 VA
	Rated grid output current(@400V)	21.7 A	29.0 A	36.2 A	43.3 A	43.4 A
	Max. grid output current	23.9 A	31.9 A	39.8 A	47.6 A	47.8 A
	Power factor at rated power / adjustable range	1 / 0.8 leading to 0.8 lagging				
	Harmonics THDi (@ Nominal power)	< 3 % (of nominal power)				
EPS output	Nominal AC voltage	3 / N / PE, 220 V / 380 V 3 / N / PE, 230 V / 400 V 3 / N / PE, 240 V / 415 V				
	Nominal output frequency	50 Hz/60 Hz				
	Rated apparent power	15000 VA	20000 VA	25000 VA	29900 VA	30000 VA
	Max. apparent power (@400 V, continuous on-grid/off-grid)	16500 VA	22000 VA	27500 VA	32890 VA	33000 VA
	Rated current(@400V)	21.7 A	29.0 A	36.2 A	43.3 A	43.4 A
	Max. current (@400 V, continuous on-grid / off-grid)	23.9 A	31.9 A	39.8 A	47.6 A	47.8 A
	Max. power on each phase (@400 V, continuous on-grid / off-grid)	5500 W	7333 W	9166 W	10963 W	11000 W
	Peak output apparent power(off-grid up to 10s)	30000 VA	40000 VA	45000 VA	45000 VA	45000 VA
	Max. switch time	< 10 ms				
	Output THDv (@ Linear load)	2 %				
Efficiency	MPPT efficiency	99.9 %				
	European efficiency / Max. efficiency	97.2 % / 98.0 %		97.9 % / 98.4 %		
Safety protection	DC / AC surge protection (Type II, according to EN/IEC 61643-11)	● / ○				
	Insulation resistance detection	●				
	PV string input reverse polarity protection	●				
	Battery input reverse polarity protection	●				
	Ground fault monitoring	●				
	Residual current monitoring unit	●				
	AC short circuit protection	●				
	Anti-islanding protection	●				
General data	Supported grid types	TN-S, TN-C, TN-C-S, TT				
	Dimensions (W / H / D)	769 mm / 491 mm / 285 mm				
	Weight	52.0 kg		58.0 kg		
	Colour	● Morandi blue / ● Earl red / ● Scandinavian grey				
	Operating temperature range	-30 °C ... +60 °C				
	Cooling concept	Smart cooling				
	Degree of protection (as per IEC 60529)	IP66				
	Max. relative humidity	100 %				
Max. operating altitude	4000 m					
Features	User interface	LED & APP				
	BMS interface	CAN				
	Communication interfaces	Dongle: WiFi (2.4 GHz) / LAN (100 Mbps) Inverter: RS485 (ModBus RTU, Sunspec RTU), LAN (100 Mbps, Modbus TCP only)				
	Digital output (dry contact) / No. of outputs	● / 3				
	Digital input (dry contact) / No. of inputs	● / 7				
	Integrated power control / export power control	● / ●				

● standard features ○ optional features - not available

Version:Nov 2024

